



USER MANUAL

Less Limiter

A brickwall limiter with a true peak ceiling, measured between samples.

macOS: AU and VST3, Apple silicon · Windows: VST3, 64 bit
mixlessaudio.com · support@mixlessaudio.com

Overview


Less Limiter is a brickwall limiter measured in true peak. Set the ceiling to -1 dBTP and the output stays under it. The measurement is BS.1770 true peak, which is what lossy encoders overshoot on, so it leaves them headroom. The gain computer runs release, sliding maximum and smoothing in an order chosen so the ceiling holds.

Installation

Run the installer for your platform. On macOS the AU and VST3 versions install for all users; on Windows the VST3 installs under Common Files. Factory presets install into your user preset folder and are never overwritten: presets you save land in the same folder and stay yours.

MACOS PRESETS	~/Library/Application Support/MixLess/Presets/Less Limiter
WINDOWS PRESETS	%APPDATA%\MixLess\Presets\Less Limiter


The interface



Press **I** in the plugin to toggle the same control descriptions as cursor tooltips.

The screen while it works

Two moments from the simplified display on the how-to page: at rest, and with material running through it. Print cannot move, so these are frames of that animation.



Controls

GAIN	Gain: drive into the limiter. More gain = louder and more limiting
CEILING	Ceiling: the level the output is held under. With TRUE PEAK on it is measured in dBTP, the way encoders see it; with TRUE PEAK off it is a sample peak in dB and inter sample peaks can still exceed it
RELEASE	Release: how fast gain comes back after limiting. Too fast distorts lows
LOOKAHEAD	Lookahead: catches transients cleanly ahead of time. Adds that much latency
TRUE PEAK	TRUE PEAK: limit inter-sample (oversampled) peaks, not just sample peaks
TP RESET	Reset the output true-peak hold readout

Workflows

Set a streaming-safe ceiling

Set Ceiling to -1 dBTP with True Peak on. Raise Gain until the loudness sits where you want it; the true peak ceiling holds at the plugin output.

Catch peaks transparently

Use the Transparent Catch preset. With the ceiling just below the peaks, only the loudest moments are touched; everything else passes unchanged, and a test asserts that on every build.

Push loudness deliberately

Raise Gain past the ceiling and listen as density grows. The release control trades punch against loudness; the meter shows exactly how much reduction you are buying.

Tips

The ceiling is a guarantee: output true peak never exceeds it in test.

True Peak mode measures inter-sample peaks per BS.1770, the same measure lossy encoders overshoot on.

Below the ceiling the limiter is a straight wire.

Specifications

FORMATS	AU, VST3
LOOKAHEAD	2 ms, 96 samples at 48 kHz, reported
DETECTION	true peak per BS.1770, switchable
FACTORY PRESETS	4

Support

Questions and problems: support@mixlessaudio.com. Legal notices, the privacy notice and third-party licences: mixlessaudio.com.